

# DesignLine Recessed Door Contact



## OVERVIEW

The DesignLine Recessed Door Contact from Interlogix is the industry's finest supervised, recessed door contact. Hidden within the door frame, the DesignLine contact is ideal, especially when a discreet sensor is required. The contact uses a replaceable lithium battery that lasts up to five years under normal usage and comes with a standard flush-mount and a flanged top.

## STANDARD FEATURES

- Compact design ensures effortless installation
- Hides discreetly in door frame
- Replaceable lithium battery lasts up to five years
- Easily installed
- Standard flush-mount and flanged tops included
- Requires only one drill bit to install
- Supervisory reports of battery and transmitter condition

## Specifications

Battery	CR2032, 3VDC, 225mAh, Lithium Coin Cell
Typical battery life	5 years
Transmitter frequency	319.508 MHz (crystal-controlled)
Transmitter frequency tolerance	+/- 8 kHz
Bandwidth	24 kHz
Modulation type	Amplitude Shift Key (ASK)
Unique ID codes	16 million
Peak field strength	Typical 30,000 uV/m @ 3m
Magnetic sensitivity of reed switch	10 to 20 amp turns
Reed sensitivity	.38-in. (.97-cm) gap
Magnet type	Nd-Fe-B, N45
Magnet dimensions (WxD)	0.7 x 0.75 in. (1.8 x 1.9 cm)
Supervisory interval	64 minutes
Operating temperature	10°F (-12°C) to 120°F (49°C)
Enclosure	PC-540
Weight	0.45 oz. (12.6g)
Dimensions (WxD)	1.55 x 0.87 in. (3.92 x 2.21 cm)
Color	Belgian Gray
FCC standard	FCC Part 15

## Ordering Information

<b>TX-1510-01-1</b>	DesignLine Recessed Door Contact
---------------------	----------------------------------